

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Currently amended): A method of determining final media selection parameters, comprising:

receiving, at a printer, a print job including a print client indicator, the print client indicator being existing information in the communication protocol being utilized to send the print job from a print client, wherein the existing information is typically not used to determine media selection parameters; and

selecting at least one of the final media selection parameters based on the existing information that is typically not used to determine media selection parameters, wherein said selecting the at least one of the media selection parameters comprises:

comparing the print client indicator to a plurality of entries in a mapping module;
determining if a matching entry including the print client indicator exists in the mapping module;
determining if the matching entry includes media selection parameters; and
outputting at least one of the media selection parameters as one of the final media selection parameters if the matching entry exists in the mapping module.

Claim 2 (Withdrawn): The method of claim 1, wherein the print client indicator is a network identity.

Claim 3 (Withdrawn): The method of claim 1, wherein the print client indicator is a Transmission Control Protocol (TCP) port number.

Claim 4 (Withdrawn): The method of claim 1, wherein the print client indicator is a modality indicator.

Claim 5 (Original): The method of claim 1, wherein the print client indicator is a text attribute.

Claim 6 (Original): The method of claim 5, wherein the text attribute is one of a username, a password, a queue name, a logical device name, an AppleTalk ID, a source file name, a destination file name, a destination directory name, a DICOM AE Title, source IP address alias, destination IP address alias, and a free form text field.

Claim 7 (Withdrawn): The method of claim 1, wherein the print client indicator is at least two of network identity, a Transmission Control Protocol (TCP) port number, a modality indicator, and a text attribute.

Claim 8 (Withdrawn): The method of claim 7, wherein the at least two of the network identity, the TCP port number, the text attribute, and the modality indicator correspond to multiple matching entries and a priority indicator determines one of the multiple matching entries that is selected along with the corresponding media selection parameters.

Claim 9 (Currently amended): A program code storage device, comprising:
a machine-readable storage medium; and machine-readable program code, stored on the machine-readable storage medium, having instructions, which when executed cause a multi-media printer to:

receive, at a printer, a print job including a print client indicator, the print client indicator being existing information in the communication protocol being utilized to send the print job from a print client, wherein the existing information is typically not used to determine media selection parameters; and

select at least one of the final media selection parameters based on the existing information that is typically not used to determine media selection parameters, wherein said selection of the at least one of the media selection parameters comprises execution of the instructions to cause the multi-media printer to:

compare the print client indicator to a plurality of entries in a mapping module;

determine if a matching entry including the print client indicator exists in the mapping module;

determine if the matching entry includes media selection parameters; and
output one of the media selection parameters as one of the final media selection parameters if the matching entry exists in the mapping module.

Claim 10 (Withdrawn): The program code storage device of claim 9, wherein the print client indicator is a network identity.

Claim 11 (Withdrawn): The program code storage device of claim 9, wherein the print client indicator is a Transmission Control Protocol (TCP) port number.

Claim 12 (Withdrawn): The program code storage device of claim 9, wherein the print client indicator is a modality indicator.

Claim 13 (Original): The program code storage device of claim 9, wherein the print client indicator is a text attribute.

Claim 14 (Previously presented): The program code storage device of claim 13, wherein the text attribute is one of a username, a password, a queue name, a logical device name, a AppleTalk ID, a source file name, a destination file name, a destination directory name, a DICOM AE Title, a source IP address alias, a destination IP address, and another free-form text field.

Claim 15 (Withdrawn): The program code storage device of claim 9, wherein the print client indicator is at least two of an Internet Protocol (IP) address, a Transmission Control Protocol (TCP) port number, a modality indicator, and a text attribute.

Claim 16 (Withdrawn): The program code storage device of claim 15, wherein the at least two of the network identity, the TCP port number, the text attribute, and the modality indicator correspond to multiple matching entries and a priority indicator determines one of the

multiple matching entries that is selected along with the corresponding media selection parameters.

Claim 17 (Previously presented): A multi-media printer to render an image from a submitted print job, comprising:

a decoding module to receive the submitted print job and to extract at least one print client indicator from the submitted print job, the print client indicator being existing information in the communication protocol being utilized to send the submitted print job from a print client, wherein the existing information is typically not used to determine media selection parameters;

a mapping module including a plurality of entries, each of the plurality of entries including at least one print client indicator and a corresponding media selection parameter; and

a parameter determination module to receive the at least one print client indicator from the decoding module, to compare the at least one print client indicator to the plurality of entries in the mapping module to determine if a matching entry corresponds to the at least one print client indicator, and to output at least one media selection parameter as one of the final media selection parameters if the matching entry is found in the mapping table.

Claim 18 (Original): The multi-media printer of claim 17, wherein the mapping module is stored on a mass storage device internal to the multi-media printer.

Claim 19 (Original): The multi-media printer of claim 17, wherein the mapping module is stored on a removable memory device.

Claim 20 (Currently amended): The multi-media printer of claim 17, wherein the mapping module is updated via [[am]] an operation panel of the multi-media printer.

Claim 21 (Original): The multi-media printer of claim 17, wherein the mapping module is updated by transmitting a file in a pre-determined format to the multi-media printer.

Claim 22 (Original): The multi-media printer of claim 17, wherein the mapping module is updated by transmitting a command from a print client.

Claim 23 (Withdrawn): The multi-media printer of claim 17, wherein the print client indicator is a TCP port number.

Claim 24 (Withdrawn): The multi-media printer of claim 17, wherein the print client indicator is a network identity.

Claim 25 (Withdrawn): The multi-media printer of claim 17, wherein the print client indicator is a modality indicator.

Claim 26 (Original): The multi-media printer of claim 17, wherein the print client indicator is a text attribute.

Claim 27 (Withdrawn): The multi-media printer of claim 17, wherein the at least one print client indicator has multiple mapping entries in the mapping module and a priority indicator identifies one of the multiple entries as the matching entry.

Claim 28 (Previously presented): A multi-media printer to render an image from a submitted print job, comprising:

- a decoding module to receive the submitted print job and to extract at least one print client indicator from the submitted print job, the print client indicator being existing information in the communication protocol being utilized to send the submitted print job from a print client, wherein the existing information is typically not used to determine media selection parameters;

- a mapping module including a plurality of entries, each of the plurality of entries including at least one print client indicator and a corresponding job settings file, and

- a parameter determination module to receive the at least one print client indicator from the decoding module, to compare the at least one print client indicator to the plurality of entries in the mapping module to determine if a matching entry corresponds to the at least one print client indicator, to determine if the job settings file in the matching entry includes at least one media selection parameter, to determine if the at least one media selection parameter is defined and operational, and to output the at least one media selection parameter as one of the final

media selection parameters if the job settings file in the matching entry is found in the mapping module.

Claim 29 (Original): The multi-media printer of claim 28, wherein the mapping module is updated by one of 1) via an operation panel; 2) transmitting a file in a pre-determined format to the multi-media printer; and 3) transmitting a command from a print client.

Claim 30 (Original): The multi-media printer of claim 28, wherein the print client indicator is one of a TCP port, a network identity, a modality indicator, and a text attribute.

Claim 31 (Withdrawn): The multi-media printer of claim 30, wherein the at least one print client indicator includes multiple, mapping entries in the mapping module and a priority indicator identifies one of the multiple entries as the matching entry.

Claim 32 (Withdrawn): A medical imaging system, comprising:

- a plurality of computing devices to transmit print jobs including print job parameters and print job data;
- a plurality of medical imaging devices to transmit print jobs including print job parameters and print job data; and
- a multi-media printer to receive the print jobs from either the plurality of computing devices or the plurality of medical imaging devices and to create an image from the print job data according to the print job parameters, wherein the multi-media printer includes
 - a decoding module to receive the submitted print job and to extract at least one print client indicator from the submitted print job;
 - a mapping module including a plurality of entries, each of the plurality of entries including at least one print client indicator and a corresponding media selection parameter, and
 - a parameter determination module to receive the at least one print client indicator from the decoding module, to compare the at least one print client indicator to the plurality of entries in the mapping module to determine if a matching entry corresponds to the at least one print client indicator, to determine if the at least one print client indicator is defined and operational,

and to output at least one media selection parameter as one of the final media selection parameters if the matching entry is found in the mapping module.

Claim 33 (Withdrawn): The medical imaging system of claim 32, wherein the at least one print client indicator has multiple mapping entries in the mapping module and a priority indicator identifies one of the multiple entries as the matching entry.

Claim 34 (Withdrawn): A medical imaging system, comprising:

- a plurality of computing devices to transmit print jobs including print job parameters and print job data;
- a plurality of medical imaging devices to transmit print jobs including print job parameters and print job data; and
- a multi-media printer to receive the print jobs from either the plurality of computing devices or the plurality of medical imaging devices and to create an image from the print job data according to the print job parameters, wherein the multi-media printer includes
 - a decoding module to receive the submitted print job and to extract at least one print client indicator from the submitted print job;
 - a mapping module including a plurality of entries, each of the plurality of entries including at least one print client indicator and a corresponding job settings file; and
 - a parameter determination module to receive the at least one print client indicator from the decoding module, to compare the at least one print client indicator to the plurality of entries in the mapping module to determine if a matching entry corresponds to the at least one print client indicator, to determine if the job settings file in the matching entry includes at least one media selection parameter, to determine if the at least one media selection parameter is defined and operational, and to output at least one media selection parameter as one of the final media selection parameters if the matching entry is found in the mapping module.

Claim 35 (Currently amended): A method of determining final media selection parameters, comprising:

receiving, at a printer, a print job including a print client indicator, the print client indicator being existing information within the print job from a print client, wherein the existing information is typically not used to determine media selection parameters; and

selecting at least one of the final media selection parameters based on the existing information that is typically not used to determine media selection parameters, wherein said selecting the at least one of the media selection parameters comprises:

comparing the print client indicator to a plurality of entries in a mapping module;
determining if a matching entry including the print client indicator exists in the mapping module;

determining if the matching entry includes media selection parameters; and
outputting at least one of the media selection parameters as one of the final media selection parameters if the matching entry exists in the mapping module.

Claim 36 (Withdrawn): The method of claim 35, wherein the print client indicator is a network identity.

Claim 37 (Withdrawn): The method of claim 35, wherein the print client indicator is a Transmission Control Protocol (TCP) port number.

Claim 38 (Withdrawn): The method of claim 35, wherein the print client indicator is a modality indicator.

Claim 39 (Previously presented): The method of claim 35, wherein the print client indicator is a text attribute.

Claim 40 (Previously presented): The method of claim 39, wherein the text attribute is one of a username, a password, a queue name, a logical device name, an AppleTalk ID, a source file name, a destination file name, a destination directory name, a DICOM AE Title, source IP address alias, destination IP address alias, and a free form text field.